

DESCRIPTION

RG-400 Uni-Directional High Performance Fiberglass Reinforcement Tape

RG-400 is an economical fiberglass reinforced tape designed for most packaging. The 1.1 mil polypropylene film combined with an aggressive ‘solventless’ pressure-sensitive adhesive provides resistance to filament delimitation and separation, excellent adhesion to corrugated cartons, and outstanding holding power. Will hand break, no knives needed.

Nominal Pipe Size	Pipe Outside dia.	O.D with RG (in.)	Circumf. w/ RG (in.)	Approx. L.F. of Tape per L.F. of Pipeline **
				Spiral Wrap Spacing (in) 6
2	2.375	3.24	10.17	1.97
4	4.5	5.36	16.84	2.98
6	6.63	7.49	23.51	4.05
8	8.63	9.49	29.80	5.07
10	10.75	11.61	36.47	6.17
12	12.75	13.61	42.76	7.2
14	14	14.86	46.68	7.85
16	16	16.86	52.97	8.89
18	18	18.86	59.25	9.93
20	20	20.86	65.53	10.97
22	22	22.86	71.82	12.02
24	24	24.86	78.10	13.06
30	30	30.86	96.95	16.19
34	34	34.86	109.52	18.29
36	36	36.86	115.80	19.33
42	42	42.86	134.65	22.47
48	48	48.86	153.50	25.61

**Multiply by Pipeline Length in ft. to get Estimated Tape Quantity in ft. (NO WASTE INCLUDED)



All the above information is given in good faith, but the figures are typical values only and should not be taken as a guarantee of performance. Manufacturing tolerances for dimensional and technical characteristics apply and are available upon request. The company reserves the right to improve the product and adjust the specification without notice.